



Rubcoat WP

Wall protection for tunnels.

RUBCOAT

SPECIAL COATINGS

One-compound, ready-to-use coating with good adhesion to Rubcoat gas and vapour-proof coating.

Product properties

Permanent protection against water, chemical and corrosive products, such as acids and oil. Wear resistant. Washable. Dirt repellent. Decorative, smooth and glossy.

Supply and storage

Rubcoat WP is supplied in 20 liter. The product has a shelf life of 1 year if the package is unopened and the storage temperature is between 5 °C a 20 °C.

Technical data

Basis : polyurethane 1-compound
Packing : 20 liter container
Colour : red-brown
Consistency : liquid
Density : 1.1
Application : roller or brush
Application temp. : +5 °C to +30 °C
Temp. resistance : -20 °C to +80 °C
Cleaning material : thinner
consumption : 4-6 m²/litre

Transport data

Transport via:
road - UN 1263 class 3
sea - UN 1263 class 3
air - UN 1263 class 3

Remarks

We draw your attention to the fact that this information sheet cancels all previous information about this product. We retain the right to make changes in the event of technical progress.

Application

As a finish and wear-resistant layer in compost tunnels on Rubcoat treated walls and floors etc.

How to apply

The substrate must be solid, dry and clean op oil and grease. Only apply the product above 5 °C and if the moisture content of the surface is less than 15%. Stir and apply in two very thin layers with an intervening time of 6 to 24 hours. Mechanically and chemically resistant after 5 days. Provide sufficient ventilation.



RUBCOAT™ is a trademark of Rubcoat B.V.

Correspondence address: P.O. Box 2086, 6020 AB Budel (NL) • Visitor's address: 't Inne 32c, 6021 DA Budel (NL)
Tel.: +31 495 49 19 16 • Fax: +31 495 49 37 50 • info@rubcoat.com www.rubcoat.com

